

## PRODUCT DATA SHEET

### EURO UTILITY™ WARNING TAPE: DETECTABLE

UKT03

Ref	TS207A
Date	OCT 2020
Pages	1 of 1

#### DESCRIPTION

Innovative warning tape which exceeds the requirements of European Standard BS EN 12613.

Made from a heavy duty, twin-ply structure of highly resistant, self-coloured plastic film, incorporating two reinforcing polypropylene bands.

Complete with two tracer wires to allow location from above ground.

#### INSTRUCTIONS / USES

When installed 300mm above an underground pipe or cable, the warning tape gives a visible warning of imminent danger when unearthed by future contractors excavating near the installation.

The unique design ensures that, when pulled from the ground, the polypropylene bands break at exactly the correct point to ensure that 200mm of the tape is visible in both the trench and the excavator's bucket.

The printed warning message is encapsulated within a protective scratchproof covering to increase longevity of the product.

#### BENEFITS / KEY FEATURES

- > Premium quality – exceeds the requirements of European Standard BS EN 12613
- > Excellent visibility in both the trench and the excavator bucket.
- > Detectable – allows location from above ground
- > Free from PVC


#### TECHNICAL INFORMATION

<b>FILM SUBSTRATE</b>	<b>INK</b>	<b>REINFORCING BAND SUBSTRATE</b>
Virgin Grade LDPE (low density polyethylene)	Highly resistant, solvent based	Polypropylene
<b>TAPE WIDTH</b>	<b>TAPE THICKNESS</b>	<b>ROLL LENGTH</b>
150mm wide	150mu (0.15mm)	100M long
<b>TRACER WIRES</b>	<b>RESISTANCE TO ACID</b>	<b>RESISTANCE TO ALKALI</b>
2 x 0.5mm diameter stainless steel	Highly resistant down to 2.5pH	Highly resistant up to 11pH
<b>COLOUR PIGMENT</b>	<b>TENSILE STRENGTH</b>	<b>ROLL WEIGHT</b>
Lead-free	947 N/mm <sup>2</sup>	Approx 3.5 kgs

#### STANDARD VERSIONS



UKT03ELEx



UKT03FOCx



UKT03GASx



UKT03WATx



UKT03POWx



UKT03STRx