

## PRODUCT DATA SHEET

### DOUBLE-SIDED TAPE: GENERAL PURPOSE

UKT84STD

Ref	TS1355A
Date	Dec 2014
Pages	1 of 1

**DESCRIPTION** Premium quality, double-sided tape.

High initial grab and good conformability.  
 Can be torn by hand to aid easier application.

Excellent adhesion to most surfaces, including metal, plastic, wood and tile.

**BENEFITS / KEY FEATURES**

- > Premium quality
- > Reliable performance
- > Conforms to irregular surfaces
- > High tack – long life expectancy

#### TECHNICAL INFORMATION

<b>SUBSTRATE</b>	<b>ADHESIVE</b>	<b>PEEL ADHESION</b>
Tissue	Synthetic rubber resin adhesive	7 N/cm
<b>TAPE WIDTH</b>	<b>TAPE THICKNESS</b>	<b>ROLL LENGTH</b>
25mm, 50mm	100 microns	50M long
<b>ELONGATION</b>	<b>TENSILE STRESS</b>	<b>COLOUR</b>
25%	7 N/cm	White
<b>WEIGHT</b>	<b>TEMPERATURE RANGE</b>	<b>SHELF LIFE</b>
25mm – 0.2 Kgs 50mm – 0.5 Kgs	-10°C to +50°C	12 months

#### OTHER INFORMATION