

Reference	HS879F
Issue Date	NOV 2016
Issue No	2
Supersedes	1
Approved by	GPL
Page	1 of 7

Product: SIGN MASKING SPRAY PAINT

1. IDENTIFICATION		
1.1 COMMERCIAL NAME	SIGN MASKING SPRAY PAINT (UKT51MASK)	
1.2 DESCRIPTION	Spray Marker Paint for lines & spot marking	
1.3 SUPPLIER	UK Tapes Ltd, Unit 14, Finch Park, Springwood Industrial Estate, Braintree, CM7 2SF. Tel: 01376 349090	
1.4 HAZARDOUS CLASSIFICATION	Extremely Flammable	

2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Aerosol, Category 1 (Aerosol 1, H222 - H229).

Repeated exposure may cause skin dryness or cracking (EUH066).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H336)

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

Mixture for aerosol application.

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms: GHS02, GHS07

Signal Word: DANGER

Product identifiers:

607-022-00-5 ETHYL ACETATE

Additional labelling:

EUH208 Contains TURPENTINE, OIL, May produce an allergic reaction.

Hazard statements :

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements - General :

P102 Keep out of reach of children.

 $\label{lem:precautionary} \textit{Precautionary statements} \cdot \textit{Prevention}:$

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

Precautionary statements - Storage :

P410 + P412 Protect from sunlight. Do no expose to temperatures exceeding 50 oC/122oF.

Other information :

Reserved for professional users.

Do not use in a confined space.

Not to be used for any usage other than those specified.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European

Chemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture satisfies neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

3. COMPOSITION / INFORMATION ON INGREDIENTS			
Mixtures Composition			
Identification	(EC) 1272/2008	Note	%
INDEX: 607-022-00-5	GHS02, GHS07	[1]	25 <= x % < 50
CAS: 141-78-6	Dgr		
EC: 205-500-4	Flam. Liq. 2, H225		
REACH: 01-2119475103-46	Eye Irrit. 2, H319		
	STOT SE 3, H336		
ETHYL ACETATE	EUH:066		



Reference	HS879F
Issue Date	NOV 2016
Issue No	2
Supersedes	1
Approved by	GPL
Page	2 nf 7

CAS: 74-98-6	GHS02	[1]	10 <= x % < 25
EC: 200-827-9	Dgr		
REACH: 01-9112486944-21	Flam. Gas 1, H220		
	Press. Gas, H280		
PROPANE			
CAS: 64742-48-9	GHS08, GHS07, GHS02		10 <= x % < 10
EC: 265-150-3	Dgr		
REACH: 01-2119463258-33	Flam. Liq. 3, H226		
	Asp. Tox. 1, H304		
DEAROMATIZED HYDROCARBONS	STOT SE 3, H336		
	EUH:066		
INDEX: 601-004-00-0	GHS02, GHS04	С	10 <= x % < 25
CAS: 106-97-8	Dgr	[1]	1.5
EC: 203-448-7	Flam. Gas 1, H220	1.1	
REACH: 01-2119474691-32	1 101111 305 1/11225		
REMON. 01 2117474071 32			
BUTANE			
CAS: 75-28-5	GHS08		2.5 <= x % < 10
EC: 200-857-2	Dgr		
REACH: 01-2119485395-27	Asp. Tox. 1, H304		
	EUH:066		
ISOBUTANE (containing less than 0.1% Butadiene)			
,			
INDEX: 650-002-00-6	GHS08, GHS07, GHS02, GHS09		0 <= x % < 1
CAS: 8006-64-2	Dgr		
EC: 232-350-7	Flam. Liq. 3, H226		
	Acute. Tox. 4, H332		
TURPENTINE, OIL	Acute. Tox. 4, H312		
	Acute. Tox. 4, H302		
	Asp. Tox. 1, H304		
	Eye Irrit. 2, H319		
	Skin Irrit. 2, H315		
	Aquatic Chronic 2, H411		
Information on ingredients :	•	<u> </u>	<u> </u>
[1] Substance for which maximum workplace exposure lim	nits are available.		

Λ FIRST ΔID

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

In the event of splashes or contact with skin:

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing:

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

5. FIRE FIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

In the event of fire, use specifically suitable extinguishing agents. Never use water. Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

In the event of a fire, use:

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)



Reference	HS879F
Issue Date	NOV 2016
Issue No	2
Supersedes	1
Approved by	GPL
Page	3 of 7

Prevent the effluent of fire-fighting measures from entering drains or waterways

Unsuitable methods of extinction

In the event of a fire, do not use:

- water
- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed:

- carbon monoxide (CO)
- carbon dioxide (CO2)

5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus

6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available

7. STORAGE & HANDLING

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Never pour water into this mixture.

Do not breathe in aerosols.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.



Reference	HS879F
Issue Date	NOV 2016
Issue No	2
Supersedes	1
Approved by	GPL
Page	4 of 7

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question: other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended:

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- PVA (Polyvinyl alcohol)

Recommended properties:

- Impervious gloves in accordance with standard EN374

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing:

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

9. PHYSICAL & CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information

Physical state : Viscous liquid

Spray.

Important health, safety and environmental information

pH: Not relevant

Boiling point/boiling range : Not specified. Vapour pressure (50°C) : Not relevant.

Density: < 1

Water solubility: Insoluble.

Melting point/melting range : Not specified. Self-ignition temperature : Not specified.

Decomposition point/decomposition range: Not specified.

Chemical combustion heat: Not specified.
Inflammation time: Not specified.
Deflagration density: Not specified.
Inflammation distance: Not specified.
Flame height: Not specified.
Flame duration: Not specified.

9.2. Other information

No data available.

10. STABILITY & REACTIVITY

10.1. Reactivity

No data available

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.



Reference	HS879F
Issue Date	NOV 2016
Issue No	2
Supersedes	1
Approved by	GPL
Page	5 of 7

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid:

- heating
- heat
- humidity

Protect from moisture. Reaction with water can cause an exothermic reaction.

10.5. Incompatible materials

Keep away from :

- water

10.6. Hazardous decomposition products

The thermal decomposition may release/form:

- carbon monoxide (CO)
- carbon dioxide (CO2)

11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness. Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Splashes in the eyes may cause irritation and reversible damage

11.1.1. Substances

Acute toxicity:

DEAROMATIZED HYDROCARBONS (CAS: 64742-48-9)

Oral route : LD50 > 5000 mg/kg

Species: Rat

Dermal route : LD50 > 5000 mg/kg

Species : Rabbit

Inhalation route (n/a): LC50 > 4951 mg/m3

Species: Rat

11.1.2. Mixture

No toxicological data available for the mixture.

12. ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Substances

DEAROMATIZED HYDROCARBONS (CAS: 64742-48-9)

Fish toxicity: LC50 > 1000 mg/l Species: Oncorhynchus mykiss Duration of exposure: 96 h Crustacean toxicity: EC50 = 1000 mg/l Species: Daphnia magna Duration of exposure: 48 h Algae toxicity: ECr50 > 1000 mg/l

Species : Pseudokirchnerella subcapitata Duration of exposure : 72 h

Aquatic plant toxicity : Species : Others

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability



Reference	HS879F
Issue Date	NOV 2016
Issue No	2
Supersedes	1
Approved by	GPL
Page	6 of 7

12.2.1. Substances

DEAROMATIZED HYDROCARBONS (CAS: 64742-48-9)

Biodegradability: no degradability data is available, the substance is considered as not degrading quickly.

DEAROMATIZED HYDROCARBONS

Biodegradability: no degradability data is available, the substance is considered as not degrading quickly.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available

12.6. Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor

Codes of wastes (Decision 2001/573/EC, Directive 2006/12/EEC, Directive 94/31/EEC on hazardous waste):

16 05 04 * gases in pressure containers (including halons) containing dangerous substance

14. TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2015 - IMDG 2014 - ICAO/IATA 2015).

14.1. UN number

1950

14.2. UN proper shipping name

UN1950=AEROSOLS, flammable

14.3. Transport hazard class(es)

- Classification: 2.1

14.4. Packing group

-

14.5. Environmental hazards

15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- Directive 75/734/CEE modified by directive 2013/10/UE
- EU Regulation No. 1272/2008 amended by EU Regulation No. 487/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 944/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 605/2014.
 EU Regulation No. 1272/2008 amended by EU Regulation No. 1297/2014.
- Container information:

No data available

- Particular provisions :

No data available.

- Standardised American system for the identification of hazards presented by the product in view of emergency procedures (NFPA 704):



Reference	HS879F
Issue Date	NOV 2016
Issue No	2
Supersedes	1
Approved by	GPL
Page	7 of 7

16. OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3:

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Abbreviations:

DNEL : Derived No-Effect Level

ADR: European agreement concerning the international carriage of dangerous goods by Road.

IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association. ICAO: International Civil Aviation Organisation

RID: Regulations concerning the International carriage of Dangerous goods by rail.

WGK: Wassergefahrdungsklasse (Water Hazard Class).

GHS02: Flame

PBT: Persistent, bioaccumulable and toxic. vPvB: Very persistent, very bioaccumulable.