

EURO UTILITY™ WARNING TAPE

UKT03

Ref	TS207
Date	Dec 2014
Pages	1 of 1

DESCRIPTION

Innovative warning tape which exceeds the requirements of European Standard BS EN 12613.

Made from a heavy duty, twin-ply structure of highly resistant, self-coloured plastic film, incorporating two reinforcing polypropylene bands.

INSTRUCTIONS / USES

When installed 300mm above an underground pipe or cable, the warning tape gives a visible warning of imminent danger when unearthed by future contractors excavating near the installation.

The unique design ensures that, when pulled from the ground, the polypropylene bands break at exactly the correct point to ensure that 200mm of the tape is visible in both the trench and the excavator's bucket.

The printed warning message is encapsulated within a protective scratchproof covering to increase longevity of the product.






BENEFITS / KEY FEATURES

- > Premium quality – exceeds the requirements of European Standard BS EN 12613
- > Excellent visibility in both the trench and the excavator bucket.
- > Free from PVC

TECHNICAL INFORMATION

FILM SUBSTRATE Virgin Grade LDPE (low density polyethylene)	INK Highly resistant, solvent based	REINFORCING BAND SUBSTRATE Polypropylene
TAPE WIDTH 150mm wide	TAPE THICKNESS 150µm (0.15mm)	ROLL LENGTH 100M long
PVC CONTENT The tape contains NO PVC	RESISTANCE TO ACID Highly resistant down to 2.5pH	RESISTANCE TO ALKALI Highly resistant up to 11pH
COLOUR PIGMENT Lead-free	TENSILE STRENGTH 947 N/mm ²	ROLL WEIGHT Approx 2.8 kgs

STANDARD VERSIONS

 UKT03ELE	 UKT03FOC	 UKT03GAS
 UKT03WAT	 UKT03POW	