

PRODUCT DATA SHEET

PIPE-DETECTA™ TAPE

UKT173SIL50

Ref	TS1870
Date	Dec 2014
Pages	1 of 1

DESCRIPTION Highly flexible, metallic self-adhesive tape made from aluminium.

INSTRUCTIONS / USES Aids location of plastic pipes within walls and behind plasterboard.

Complies with NHBC Standard that requires

"Where plastic pipework is in or behind wall surfaces, and would otherwise not be located by a metal detector or similar equipment, a metallic tape should be applied."

For best results, the metallic tape should be applied to the surface of the wall directly behind the pipe. Adhering the tape to the plastic pipe should be avoided unless the adhesive is approved by the pipe manufacturer.

TECHNICAL INFORMATION

TAPE WIDTH	ROLL LENGTH	FOIL THICKNESS
50mm	45M	30 microns (0.03mm)
TOTAL THICKNESS (incl adhesive)	PEEL ADHESIVE TO STEEL	LOOP TACK
60 microns (0.06mm)	1000 N/M	800 N/M
SHEAR (STATIC)	FIRE PROTECTION	APPLICATION TEMPERATURE
87 hours @ 1 Kg	Conforms to Class O – BS476	0°C to 35°C
SERVICE TEMPERATURE	ELONGATION	ROLL WEIGHT
-20°C to 120°C	5%	0.42 Kgs

OTHER INFORMATION PIPE-DETECTA™ is a trade name of UK Tapes Ltd