

PRODUCT DATA SHEET

ISO 14726 PIPE MARKING TAPE

UKT21ISO

Ref	TS459A
Date	Dec 2014
Pages	1 of 1

DESCRIPTION

Pipeline identification tape produced from a high specification vinyl & polypropylene laminate.

Marine & ship grade marking tape. It is not intended for external use (please see our product UKT24 'ANYWEATHER'™ Pipeline Tape if you require an external pipe marking tape).

The tape demonstrates excellent resistance to acids & alkalis and the printing is protected by a 'scratch-resistant' covering of transparent plastic.

The tape is colour-coded to ISO 14726 requirements

INSTRUCTIONS / USES

Designed to label pipework to help eliminate errors and accidents.

To apply, ensure that the pipe surface is clean, dry and free from dust, grease or other contaminants. Unwind the tape and apply around the full circumference of the pipe. Overlap by at least 25mm.

BENEFITS / KEY FEATURES

- > Durable, twin-layer construction
- > Scratch-proof / wipe-clean covering surface
- > Colour-coded to ISO 14726 requirements

TECHNICAL INFORMATION

BASE SUBSTRATE
Vinyl

COVERING SUBSTRATE
Transparent Polypropylene

ADHESIVE
Solvent – Rubber based

ROLL SIZE
50mm x 33M

TAPE THICKNESS
90mu (0.09mm)

SHELF LIFE
12 months

RESISTANCE TO UV
Moderate

TENSILE STRENGTH
214 N/25mm

SERVICE TEMPERATURE
-10°C to + 50°C

STANDARD VERSIONS		
<p>Black RAL 9005</p>  <p>UKT21ISOBLK50</p>	<p>Blue RAL 5015</p>  <p>UKT21ISOBLU50</p>	<p>Brown RAL 8001</p>  <p>UKT21ISOBRN50</p>
<p>Green RAL 6018</p>  <p>UKT21ISOGRN50</p>	<p>Grey RAL 7001</p>  <p>UKT21ISOGRY50</p>	<p>Maroon RAL 8015</p>  <p>UKT21ISOMAR50</p>
<p>Orange RAL 2003</p>  <p>UKT21ISOORG50</p>	<p>Red RAL 3000</p>  <p>UKT21ISORED50</p>	<p>Violet RAL 4001</p>  <p>UKTISOVIO50</p>
<p>White RAL 9010</p>  <p>UKT21ISOWHT50</p>	<p>Yellow RAL 1021</p>  <p>UKT21ISOYEL50</p>	<p>Directional Arrows</p>  <p>UKTISOARR50</p>

INK
Highly resistant, solvent based

RESISTANCE TO ACID
Highly resistant

PEEL ADHESION
295 g/25mm

APPLICATION TEMPERATURE
+5°C to + 40°C

CORE
76mm diameter cardboard core

RESISTANCE TO ALKALI
Highly resistant

ROLL WEIGHT
Approx 0.19 Kg

STORAGE TEMPERATURE
+10°C to + 25°C