

## BRITE™ REFLECTIVE TAPE: UTILITY GRADE UKT26RW

Ref	TS 529 M
Date	July 2023
Pages	1 of 1



- Flexible, self-adhesive reflective marking tape
- Specifically for use on signs, bollards, gates & vehicles
- Engineering grade – Class RA1 (old BS 873 Class 2)
- Shines brightly in darkness when a light is directed at it
- Waterproof, **non-prismatic** retroreflective
- High-visibility, hazard warning diagonal stripes
- Excellent reflectivity yet low cost

### TECHNICAL INFORMATION

<b>SUBSTRATE</b> PET (Polyethene terephthalate)	<b>ADHESIVE</b> Solvent-based acrylic	<b>CORE</b> 76mm diameter cardboard core	
<b>TAPE WIDTH</b> 50mm – 200mm (other widths available on request)	<b>TAPE THICKNESS</b> 140µ (0.14mm)	<b>ROLL LENGTH</b> 10M, 25M or 45M	
<b>GRADE</b> Utility / Engineering Grade (Class RA1)	<b>SURFACE</b> Non-prismatic	<b>ADHESIVE STRENGTH</b> 15 N/25 mm FINAT-TM1 after 24h, stainless steel	
<b>LIFE EXPECTANCY</b> 5 years (subject to conditions)	<b>APPLICATION TEMPERATURE</b> 10°C - 40°C	<b>SHELF LIFE</b> 12 months	
<b>COEFFICIENT OF RETRO-REFLECTION</b>			
Observation Angle	Entrance Angle	Colour	cd / lux / M <sup>2</sup>
0.2°	5°	White	80

### OTHER INFORMATION

BRITE™ REFLECTIVE TAPE is a trade name of UK Tapes Ltd

For best results, apply in temperatures of not less than 10°C. Ensure the surface is clean, dry and free from dust, grease, oils etc. Remove the backing paper, unroll the tape and apply pressure evenly to ensure a firm bond.

The reflective data and colours at daylight comply with the international specifications for reflective materials of this class, such as EN 12899-1 Classes RA1, CR2 (Europe), DIN 67520 and DIN 6171 (Germany), BS 873: Part 6 (Great Britain), NFP 98-520 (France), SN 640878 (Switzerland), ASTM D 4956 (US), JIS Z 9117 (Japan).