

## PRODUCT DATA SHEET

### TWININATE™ PRINTED, SELF-ADHESIVE TAPE

UKT30

Ref	TS585D
Date	March 2023
Pages	1 of 1

#### DESCRIPTION

High quality, self-adhesive marking tape available with a range of different high-visibility texts printed along its length.

Made from twin-ply construction of a premium quality, self-adhesive vinyl base layer laminated with a transparent, protective polypropylene covering.

The wipe-clean, scuff-proof finish extends durability of the product.

50+ different pre-printed versions available from stock. Custom printed variations made-to-order.

#### INSTRUCTIONS / USES

100s of uses from highlighting hazards, warning of potentially dangerous materials, marking pipework, identifying dry-lining installations, floor marking, plus much more

#### BENEFITS / KEY FEATURES

- > High visibility: instant warning
- > Made from a heavy-duty, twin-ply construction for extra durability
- > Scuff-proof covering

TWININATE™ is a trade name of UK Tapes Ltd

#### TECHNICAL INFORMATION

<b>BASE SUBSTRATE</b>	<b>COVERING SUBSTRATE</b>	<b>ADHESIVE</b>
Premium quality vinyl	Transparent Polypropylene	Solvent – Rubber based
<b>SHELF LIFE</b>	<b>INK</b>	<b>CORE</b>
12 months	Highly resistant, solvent based	76mm diameter cardboard core
<b>TAPE WIDTH</b>	<b>TAPE THICKNESS</b>	<b>ROLL LENGTH</b>
48mm	90µ (0.09mm)	33M long
<b>RESISTANCE TO UV</b>	<b>RESISTANCE TO ACID</b>	<b>RESISTANCE TO ALKALI</b>
Moderate	Highly resistant	Highly resistant
<b>TENSILE STRENGTH</b>	<b>PEEL ADHESION</b>	<b>ROLL WEIGHT</b>
214 N/25mm	295 g/25mm	Approx 0.19 Kg (48mm)
<b>SERVICE TEMPERATURE</b>	<b>APPLICATION TEMPERATURE</b>	<b>STORAGE TEMPERATURE</b>
-10°C to + 50°C	+5°C to + 40°C	+10°C to + 25°C