

SUREFOOT™ ANTI SLIP TAPE

UKT80

Ref	TS299A
Date	Dec 2014
Pages	1 of 1

DESCRIPTION

Premium quality, self-adhesive, non-slip tape with an abrasive surface to help reduce the risk of slips and falls.

Made from a tough, waterproof PVC base impregnated with aluminium oxide crystals.

INSTRUCTIONS / USES

Creates a non-slip surface for steps, stairs, ramps and slippery surfaces.

INSTALLATION : Apply in temperatures of not less than 5°C, ensuring the surface is clean, dry and free from dust, grease, oil or other contaminants. Apply a brushed coating of UKT79 Primer to the ground surface and allow to almost dry. Remove the backing paper and unroll the tape, applying even pressure to ensure a firm bond. Pay particular attention to the edges of the tape. For best results, a bead of UKT79 Edge Sealer should be applied along the exposed edges. Allow at least one hour (preferably 24 hours) before walking/driving over the tape.

BENEFITS / KEY FEATURES

- > Premium quality
- > Tough, durable and long-lasting
- > High level of "Coefficient of Friction" (the accepted measurement of non-slip grip)
- > Will adhere to most surfaces

STANDARD VERSIONS

PLAIN COLOURS			STRIPED COLOURS
Black	Hi Viz Yellow	Grey	Black & Yellow Red & White
Transparent	Dull Yellow	Orange	
White	Blue	Brown	
Red	Green		
TAPE WIDTHS			ROLL LENGTH
25mm	100mm	300mm	18M long
50mm	150mm	450mm	
75mm	200mm		

TECHNICAL INFORMATION

TAPE THICKNESS	ADHESIVE	CORE
700mu (0.70mm) excluding liner	Solvent Acrylic	76mm diameter cardboard core
ELONGATION	TENSILE STRENGTH	ADHESION TO STEEL
25%	6 Kg /25mm ²	1.5 Kg /25mm ²
RESISTANCE TO WATER	RESISTANCE TO CHEMICALS	TEMPERATURE RANGE
10 months (PSTC-35)	8 months (PSTC-35)	-30°C to +70°C
COEFFICIENT OF FRICTION	COEFFICIENT OF FRICTION	ROLL WEIGHT
98 (Dry surface)	68 (Wet surface)	0.80 Kgs (based on 50mm x 18M)

OTHER INFORMATION

SUREFOOT™ is a trade name of UK Tapes Ltd