

## PRODUCT DATA SHEET

### POLYTHENE JOINTING TAPE : DOUBLE SIDED

UKT87

Ref	TS1397
Date	Dec 2014
Pages	1 of 1

#### DESCRIPTION

Double-sided, waterproof sealing strip primarily used to join damp proof membranes and other plastic sheeting.

High performance sealing & jointing tape with good elasticity and recovery properties. The soft composition makes the product highly conformable for use on irregular surfaces. The tape offers good adhesion to a wide range of substrates, specifically polyethylene.

The butyl rubber composition has excellent UV resistance and remains flexible throughout the service life of the tape.

#### INSTRUCTIONS / USES

Used to join damp proof membranes and other plastic sheeting.

**INSTALLATION :** Ensure the plastic sheeting is clean and dry before application. Apply with even force onto one sheet of plastic, peel off the backing liner and firmly press down the other sheet ensuring no air bubbles or wrinkles.

#### BENEFITS / KEY FEATURES

- > Waterproof
- > High tack adhesion – even on tricky substrates such as polythene
- > Supplied in handy 10M rolls

#### TECHNICAL INFORMATION

<b>TAPE WIDTH</b>	<b>TAPE THICKNESS</b>	<b>ROLL LENGTH</b>
50mm wide	1mm thick	10M long
<b>CARTON QUANTITY</b>	<b>SHELF LIFE</b>	<b>CORE SIZE</b>
12 rolls	12 months	35mm
<b>SUBSTRATE</b>	<b>DYNAMIC SHEAR ADHESION</b>	<b>TENSILE ADHESIVE</b>
Cross linked Butyl Rubber	13 N/CM <sup>2</sup>	19 N/CM <sup>2</sup>
<b>PEEL ADHESION</b>	<b>SPECIFIC GRAVITY</b>	<b>VAPOUR TRANSMISSION RATE</b>
12 N/CM <sup>2</sup>	1.6 g/cm <sup>3</sup>	0.16 g/m <sup>2</sup> /24hr/mm
<b>APPLICATION TEMPERATURE</b>	<b>SERVICE TEMPERATURE</b>	<b>SHELF LIFE</b>
5°C to 40°C	-40°C to 90°C	12 months