

PTFE PIPETHREAD TAPE

UKT94WHT12

Ref	TS1495
Date	Dec 2014
Pages	1 of 1

DESCRIPTION

Premium quality, non-adhesive tape made from PTFE (Polytetrafluoroethylene).

The Plumber's tape

Complies with BS 7786

Non-curing

Temperature resistant up to 250°C.

Supplied on a handy, plastic spool.

USES

Thread-sealing for engines, fuel lines, air-conditioning units, radiators, fuel tanks, vacuum lines, coolant lines, brake lines and hydraulic systems.

Suitable for use on all pipe materials.

BENEFITS / KEY FEATURES

- > Premium quality
- > Provides a gas-tight, waterproof seal on a variety of pipe threads
- > Clean and easy to use
- > Instant sealing

TECHNICAL INFORMATION

SUBSTRATE	COLOUR	CORE
PTFE (Polytetrafluoroethylene)	White	Plastic spool
TAPE WIDTH	TAPE THICKNESS	ROLL LENGTH
12mm wide	75µm (0.075mm)	12M long
PVC CONTENT	RESISTANCE TO ACID	RESISTANCE TO ALKALI
The tape contains NO PVC	Highly resistant down to 2.5pH	Highly resistant up to 11pH
TEMPERATURE RANGE	SHELF LIFE	CARTON QUANTITY
-20°C to +250°C	12 months	100 rolls

OTHER INFORMATION